CORNING


The future flows through Corning[®] Advanced-Flow[™] Reactors

G1 Process Development System

CORNING

CORNING Advanced-Flow[®] Reactors





G1 Process Development System

Features

- Flexible and versatile system designed for process development
- Compatible with any type of G1 reactor, based on glass or SiC fluidic modules
- Up to 4 liquid dosing lines and 1 gas line, offering various materials of construction for chemical compatibility
- Flow control through reactant vessel weight measurement
- Control system with touch screen interface enabling an easy control of main features


Boundary Condition

Flow Rate	Temperature	Pressure
Up to 200 ml/min	-60°C/200°C	Up to 18 bar



CORNING

CORNING





G1 SiC Reactor



Control System





Residence Time Distribution 50 x better* *compared to batch reactors

G1 Process Development System Description

Item Type	Included with the full package system (other options available on request)
Reactor	1 G1 10 FM (SiC, Glass, or Hybrid)
Main Dosing Unit	2 balances for flow control 1 liquid dosing line 0-100ml/min - Wetted materials: PFA, PTFE 1 liquid dosing line 0-100ml/min - Wetted materials: Titanium, PFA, PTFE 1 gas line - Wetted materials: stainless steel
Optional Dosing Unit	2 balances for flow control 1 liquid dosing line 0-100ml/min - Wetted materials: PFA, PTFE 1 liquid dosing line 0-100ml/min - Wetted materials: Titanium, PFA, PTFE
Control System	Based on Siemens automation devices
Downstream	Metal free back pressure regulator
Thermostats	Compatible utilities solution depending on temperature requirements

CORNING





進階官網 FB粉絲團

